


RONDA startech 4000

Multifunctions with Big Date,
Alarm, 2nd Time Zone

Caliber 4210.B – 12½'''



Product Specifications

Analog quartz movement

Line

startech

Caliber

4210.B

Size

12½'''

Version Swiss Made
Swiss Parts

8 Jewels / gold plated
4 Jewels / nickel plated

Standard battery life

54 months

Hand fitting height

2

Features

- Repairable metal watch movement
- Very long battery life
- Power saving mechanism with pulled out stem: Reduction of consumption approximately 70%
- Very easy handling by one pusher

Functions

- 1 eye
- Multifunction
- Second time zone
- Big date

Technical Specifications

Diameter Total	28.60 mm
Case fitting	28.00 mm
Movement height	4.40 mm
Height over standard battery	4.40 mm
Movement rest	0.60 mm
Height over stem	1.90 mm
Length of stem travel	0.90 mm
Stem thread	0.90 mm
Standard battery	395
Standard battery life	54 months
Battery voltage	1.5 V
Current consumption – typical	1.32 µA (Date Mechanism not in Gear)
Current consumption – maximum	1.65 µA (Date Mechanism not in Gear)
Useful torque second – typical	6 µNm
Useful torque minute – typical	300 µNm
Operating temperature	0 - 50 °C
Instantaneous rate	-10/ +20 sec/month
Resistance to magnetic fields	18.8 Oe
Resistance against shock	NIHS 91-10

Watch production

- Drawing Casing ring (standard, PDF)
- Drawing Dial (stem 3h, calendar 12h, PDF)
- Drawing Hand fitting (hand height 1, 3, PDF)
- Drawing Stem
- Casing information (PDF)
- Movement holders for T2 (PDF)

User's manual

- User's manual (PDF)

Watch repairs

- Technical instruction up to code M (PDF)
- Technical instruction as of code N (PDF)

